

## Product Information

Application Tape based on a special high tensile impregnated paper coated with a natural rubber (Medium Tack). The tape is suitable for transferring lettering and symbols cut from all qualities of self adhesive vinyls.

Especially to be emphasised are the following properties:

- Ageing- and UV-stabilised natural rubber.
- The Application Tape is easy to unroll and position and will not stretch or curl.
- Constant adhesion within a small tolerance.
- Suitable for wet application.

## Technical Data

|                         |                            |          |
|-------------------------|----------------------------|----------|
| <b>Carrier:</b>         | Special paper, impregnated |          |
| <b>Adhesive:</b>        | Natural rubber             |          |
| <b>Adhesion [N/cm]:</b> | 2,10                       | +/- 10 % |
| <b>Thickness [mm]:</b>  | 0,10                       | +/- 5 %  |

## Standard Dimensions

1.220 mm x 100 m  
1.220 mm x 91,4 m  
1.000 mm x 100 m  
1.000 mm x 91,4 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.